

LED line PRIME

Code: 217591

EAN: 5905378217591

Suntis Solar Wall Light 3000K 220lm
2Ah USB-C Square IP54 Black PRIME

New

Suntis solar facade setting from LED line PRIME offers effective lighting at 3,000 K colour temperature, generating a light stream of 220 lumens. Equipped with a Li-Ion 2000 mAh battery, it provides up to 9 hours of operation on one charge. Thanks to the IP54 class, it is resistant to atmospheric conditions. Its modern, square design made of durable ABS material perfectly fits into external arrangements.



Technical data

Parameter	Value
Warranty	5
Voltage	• 3.7 V DC
Correlated colour temperature	• 3000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP54
IK protection rating	06
IEC protection class	III
Luminous flux	220
Lifetime L70B50	30 000 h
Wyniki tłumaczenia Functional description of the daylight sensor [LUX]	50 lx-ON
Photo cell power	1.8
Photo cell current	0,37
Type of battery	LI-Ion 3.7V 2000mAh 18650

Parameter	Value
Beam angle	120
Sensor type	PIR
LED quantity	40
Lifespan	35 000 h
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Outside
Length	114 mm
Width	120,5 mm
Height	80 mm
Weight	0,4 kg
Battery life	9 h
Colour	Czarny
Material (housing)	ABS

LED line PRIME


Code: 217591

EAN: 5905378217591

Suntis Solar Wall Light 3000K 220lm
2Ah USB-C Square IP54 Black PRIME

Technical drawing


Light distribution



Additional product photos




Logistics data




Single packaging

Quantity	1
Width	125 mm
Height	85 mm
Length	125 mm
Weight	0,7 kg



Bulk packaging

Quantity	12
Width	265 mm
Height	200 mm
Length	405 mm
Weight	8,7 kg



Europallet

Height	1,90 m
Quantity in layer	4
Number of layers	8
Bulk quantity	384
Weight	220 kg

LED line PRIME

Code: 217591

EAN: 5905378217591

**Suntis Solar Wall Light 3000K 220lm
2Ah USB-C Square IP54 Black PRIME**

Example application

