

LED line PRIME

Code: 479587

EAN: 5907777479587

**Hermetic luminaire LINKER 4000K 21W
3150lm IP65 60cm gray PRIME**



LINKER 21W LED line PRIME is an advanced lighting solution with high light performance of 3150 lumens at 150 lm/W. It offers the colour of light 4000K, which provides natural color reproduction ($R_a \geq 80$). IP65 leak class and impact resistance IK08 increase its durability under difficult conditions.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5/7*
Power	• 21 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	08
IEC protection class	I
Luminous efficacy	150
Luminous flux	3150
The lumen maintenance factor	96
Lifetime L70B50	100 000 h
L80B* – difference B10–B50 \approx 1% (according to LightingEurope) – negligible	75000 h
L90B* – difference B10–B50 \approx 1% (according to LightingEurope) – negligible	50000 h

Parameter	Value
Survival factor	0.9
Colour consistency in McAdam ellipses	≤ 6
Frequency of the supply voltage	50/60Hz
Beam angle	120
Lifespan	100 000 h
Power Factor	0,95
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	$-25 \div 45$
Length	600 mm
Width	72 mm
Height	61 mm
Weight	1,9 kg
Colour	Grey
Material (housing)	Polycarbonate
Material (cover)	Polycarbonate


LED line PRIME

Code: 479587

EAN: 5907777479587

**Hermetic luminaire LINKER 4000K 21W
3150lm IP65 60cm gray PRIME**

Technical drawing



Light distribution

Additional product photos



Logistics data



Single packaging

Quantity	1
Width	75 mm
Height	65 mm
Length	630 mm
Weight	0,69 kg



Bulk packaging

Quantity	20
Width	355 mm
Height	323 mm
Length	648 mm
Volume	0,074 m3
Weight	14 kg



Europallet

Quantity	240
Height	1500 mm
Quantity in layer	
Number of layers	
Bulk quantity	12
Weight	193 kg

LED line PRIME

Code: 479587

EAN: 5907777479587

**Hermetic luminaire LINKER 4000K 21W
3150lm IP65 60cm gray PRIME**

Example application