

LED line PRIME

Code: 203983

EAN: 5905378203983

LED line PRIME FUSION linear lamp  
20W 4000K 2600lm 30\*90° white



The FUSION 20W 4000K linear housing from the LED line PRIME is designed to provide efficient and even lighting in different spaces. It offers a light stream of 2,600 lumens and 130 lm/W efficiency, which translates into low energy consumption. Its lighting angle is 30x90°, allowing precise illumination of selected areas.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 20 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	08
IEC protection class	I
Luminous efficacy	130
Luminous flux	2600
The lumen maintenance factor	96
Lifetime L70B50	50 000 h

Parameter	Value
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Sling length	200 cm
Standby power	0
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Beam angle	30 x 90
Power Factor	0,9
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
Length	586
Width	70
Height	52

LED line PRIME

Code: 203983


EAN: 5905378203983

LED line PRIME FUSION linear lamp  
20W 4000K 2600lm 30\*90° white




Technical drawing

Light distribution

Additional product photos



Logistics data



Single packaging

Width	586 mm
Height	52 mm
Length	70 mm
Weight	1,14 kg

Bulk packaging

Quantity	12
Width	690 mm
Height	260 mm
Length	260 mm
Volume	0,046 m3
Weight	13,93 kg
Comments	

Europallet

Quantity	288
Height	1710 mm
Quantity in layer	48
Number of layers	6
Bulk quantity	288
Weight	672 kg

---

LED line PRIME

Code: 203983

EAN: 5905378203983

**LED line PRIME FUSION linear lamp  
20W 4000K 2600lm 30\*90° white**

---

**Example application**