

LED line LITE


Code: 207462

EAN: 5905378207462

Park Luminaire PARKLITE 50-80-100W
CCT 6000-12000lm black LITE



PARKLITE 50-100W park housing, characterized by a light stream of between 6000 and 12,000 lumens, provides a light performance of 120 lm/W. Made of durable aluminum and equipped with hardened glass, high class IP65 tightness and IK08 resistance. He works at 220-240 V AC. It allows different light colour temperature: 3000 K, 4000 K and 6000 K. It has a high PF power factor of 0.9 and low flickering (PstLM <1).



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Power	50 W 80 W 100 W
Voltage	220-240 V AC
Correlated colour temperature	3000 K 4000 K 6000 K
Colour of the light	White
Colour rendering index Ra	80
IK protection rating	08
IEC protection class	I
Luminous efficacy	120
Luminous flux	6000-12000
The lumen maintenance factor	96
Lifetime L70B50	25 000 h
Survival factor	0,9
Colour consistency in McAdam ellipses	≤6
ULOR	2,3 %
Wire length	400 mm

Parameter	Value
Mounting type	Lighting pole ø 60mm
Frequency of the supply voltage	50/60Hz
Fixture's diameter	382
Beam angle	100
LED type	SMD LED 2835
LED quantity	384
Power Factor	0,9
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-30÷50
Length	382
Width	382
Height	117
Weight	2130
Colour	Czarny
Material (housing)	Aluminium
Material (cover)	tempered glass

LED line LITE


Code: 207462

EAN: 5905378207462


Park Luminaire PARKLITE 50-80-100W
CCT 6000-12000lm black LITE

Technical drawing




Light distribution



Additional product photos



Logistics data



Single packaging

Width	420 mm
Height	135 mm
Length	425 mm
Weight	2,25 kg

Bulk packaging

Quantity	4
Width	445 mm
Height	430 mm
Length	550 mm
Volume	0,105 m3
Weight	9,3 kg

Europallet

Height	1780 mm
Quantity in layer	8
Number of layers	4
Bulk quantity	32
Weight	74,4 kg

LED line LITE

Code: 207462

EAN: 5905378207462

**Park Luminaire PARKLITE 50-80-100W
CCT 6000-12000lm black LITE**

Example application