

LED line LITE


Code: 201415

EAN: 5905378201415

Ceiling Light 4000K 18W 1550lm round IP44 white LITE



18W LITE LED Plate is an innovative setting for excellent light quality. Generates a light stream of 1550 lm, which ensures effective lighting with a light output of 86 lm/W. Color temperature 4000K offers neutral light, ideal for various applications. IP44 leak class protects against water and dust, and Ra >80 colour rendering rate enables faithful color reproduction.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 18 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP44
IEC protection class	I
Luminous efficacy	86
Luminous flux	1550
The lumen maintenance factor	96

Parameter	Value
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD 2835
LED quantity	21
Ambient temperature suitable for operation	-20÷40
Height	58
Fixture's diameter	350 mm
Weight	410
Colour	White


LED line LITE

Code: 201415


EAN: 5905378201415

**Ceiling Light 4000K 18W 1550lm round
IP44 white LITE**

Technical drawing





Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	380 mm
Height	380 mm
Length	70 mm
Weight	0,38 kg

Bulk packaging

Quantity	12
Width	490 mm
Height	405 mm
Length	790 mm
Volume	0,156 m ³
Weight	4,91 kg
Comments	

Europallet

Height	1620 mm
Quantity in layer	24
Number of layers	4
Bulk quantity	96
Weight	39,28 kg

LED line LITE

Code: 201415

EAN: 5905378201415

**Ceiling Light 4000K 18W 1550lm round
IP44 white LITE**

Example application

