

LED line LITE Code: 201415 EAN: 5905378201415

LED line LITE Ceiling lamp PLAFON 18W 4000K 1550lm IP44





18W LITE LED Plate is an innovative setting for excellent light quality. Generates a light stream of 1550 lm, which ensures effective lighting with a light output of 86 lm/W. Color temperature 4000K offers neutral light, ideal for various applications. IP44 leak class protects against water and dust, and Ra >80 colour rendering rate enables faithful color reproduction.











Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 18 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP44
IEC protection class	1
Luminous efficacy	86
Luminous flux	1550
The lumen maintenance factor	96


Parameter	Value
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Fixture's diameter	350 mm
Beam angle	120
LED type	SMD 2835
LED quantity	21
Ambient temperature suitable for operation	-20÷40
Height	58
Weight	410
Colour	White




LED line LITE Code: 201415 EAN: 5905378201415

LED line LITE Ceiling lamp PLAFON 18W 4000K 1550lm IP44

Technical drawing



Light distribution



Additional product photos












Logistics data







Single packaging

Quantity	1
Width	380 mm
Height	380 mm
Length	70 mm
Weight	0,38 kg

Bulk packaging

Quantity	12
Width	490 mm
Height	405 mm
Length	790 mm
Volume	0,156 m3
Weight	4,91 kg
Comments	

Europallet

Height	1620 mm
Quantity in layer	24
Number of layers	4
Bulk quantity	96
Weight	39,28 kg



LED line LITE Code: 201415 EAN: 5905378201415

LED line LITE Ceiling lamp PLAFON 18W 4000K 1550lm IP44

Example application

