

LED line PRIME


Code: 217027

EAN: 5905378217027

ESTADIO 200W 5000K 90° 170lm/w  
CRI80 PRIME



The stadium ESTADIO 200W is an advanced lighting solution characterized by light performance of 170 lm/W. Thanks to the colour of the light 5000 K and the colour rendering factor CRI 80, it provides excellent lighting quality. IP66 leak class and IK10 resistance guarantee durability under difficult external conditions. Powered by 100-277 V AC voltage, the housing offers a low PF power factor of 0.95.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	B
Warranty	5
Power	• 200 W
Voltage	• 100-227 V AC
Correlated colour temperature	• 5000 K
Colour of the light	White
IP protection rating	IP66
IK protection rating	10
IEC protection class	I
Luminous efficacy	170
Luminous flux	34000
The lumen maintenance factor	96
Lifetime L70B50	100 000 h

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
CRI colour rendering index	80
Beam angle	90
LED type	EMC5050
LED quantity	100
Power Factor	0,95
Lamp's warm-up time to 60%	0,5
Ambient temperature suitable for operation	-40 / +45
For indoor use	Outside
Material (housing)	Aluminium
Material (cover)	Polycarbonate


LED line PRIME

Code: 217027

EAN: 5905378217027

**ESTADIO 200W 5000K 90° 170lm/w  
CRI80 PRIME**

**Technical drawing**




**Light distribution**


**Additional product photos**




**Logistics data**



**Single packaging**



**Bulk packaging**



**Europallet**

---

LED line PRIME

Code: 217027

EAN: 5905378217027

**ESTADIO 200W 5000K 90° 170lm/w  
CRI80 PRIME**

---

**Example application**