


LED line PRIME

Code: 249167

EAN: 5901583249167

LED line® strip 600 SMD 12V 4000K
9,6W 5mm WPCB



Technical data

Parameter	Value	Parameter	Value
Luminous efficacy	77 lm/W	Compatible dimmer type	PWM
Colour of the light	White	Laminate (colour)	White
Energy efficiency class 2019/2015	G	Laminate (thickness)	4
Colour consistency in MacAdam ellipses	≤3	LED quantity (lm)	120
IP protection rating	IP20	Cutting section	2,5
Warranty (years)	5	Type of adhesive tape	3M 300 LSE
Dimmable function	PWM	Lifespan	100000
Survival factor	0.9	Number of on/off cycles	50000
Minimum purchase quantity	5	Colour consistency in MacAdam ellipses	≤3
Lifetime L70B50	50 000	Ambient temperature suitable for operation	-20÷45 °C
Wattage (lm)	9,6 W	For indoor use	Inside
Luminous flux (lm)	680lm	IEC protection class	III
Current (lm)	0,8	Full box quantity	75 pc
Colour rendering index Ra	90	Lamp's warm-up time to 60%	1
CRI colour rendering index	90	Width	5 mm
Metres per roll	5	Height	2,5 mm
The lumen maintenance factor	96 %	Energy class	A
Beam angle	120 °	Power	• 9.6
LED type	SMD2216	Voltage	• 12 V DC
Not dimmable	TAK	Correlated colour temperature	• 4000 K

LED line PRIME


Code: 249167

EAN: 5901583249167

LED line® strip 600 SMD 12V 4000K
9,6W 5mm WPCB

Dimensions


Light distribution



Additional product photos




Logistics data



Single packaging


Width	153 mm
Height	15 mm
Length	153 mm
Weight	0,11 kg

1



Bulk packaging

Number of pieces/tape in meters pack zb	40 szt.
Width	360 mm mm
Height of collective packaging	180 mm
Length	320 mm mm
Weight	4,6 kg kg
Volume	0,020 m3 m3



Europallet

Number of pieces/tapes in meters euro pallet	12000 m
Quantity collective euro pallet	2400 szt.
Weight of a euro pallet	301,0 kg
Pallet height	1800 mm
Quantity in 1 layer	240 szt.
Number of layers	10

LED line PRIME

Code: 249167

EAN: 5901583249167

**LED line® strip 600 SMD 12V 4000K
9,6W 5mm WPCB**

Example application