

LED line

product_card.label_product_code: 200128
product_card.label_product_gtin: 5905378200128

LED line Elida 40W 4000K 120lm/W 100-277V AC T2



product_card.label_technical_data

product_card.label_attribute_name	product_card.label_attribute_value
ULOR	0 %
Luminous efficacy	120 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	4800 lm
Colour consistency in McAdam ellipses	≤5
IP protection rating	IP65
Warranty (years)	5
Survival factor	0.9
Lifetime L70B50	50 000
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
CRI colour rendering index	80
The lumen maintenance factor	96 %
Beam angle	80 x 155 °

product_card.label_attribute_name	product_card.label_attribute_value
Material (cover)	tempered glass
Material (housing)	aluminum
LED type	SMD2835
LED quantity	64
Lifespan	50000
Power Factor	0,95
Colour consistency in McAdam ellipses	≤5
Ambient temperature suitable for operation	-40÷50 °C
For indoor and outdoor use	YES
IEC protection class	I
IK protection rating	08
Lamp's warm-up time to 60%	1
Power	40 W
Voltage	100-277 V AC
Correlated colour temperature	4000 K

LED line

product_card.label_product_code200128

product_card.label_product_gtin:5905378200128


LED line Elida 40W 4000K 120lm/W 100-277V AC T2

product_card.label_dimensions

product_card.label_curve_light


product_card.label_product_gallery

product_card.label_logistic_data




product_card.label_single_package

Width	320
Height	70 mm
Length	490 mm
Weight	3,3 kg
	1



product_card.label_collective_package

Number of pieces/tape in meters pack zb	4
Width	385 mm
Height of collective packaging	385
Length	515 mm
Weight	14 kg



product_card.label_europalette

Number of pieces/tapes in meters euro pallet	60
Quantity collective euro pallet	15
Weight of a euro pallet	267 kg
Pallet height	1725
Quantity in 1 layer	5
Number of layers	3

LED line

product_card.label_product_code200128

product_card.label_product_gtin:5905378200128

LED line Elida 40W 4000K 120lm/W 100-277V AC T2

product_card.label_realization_photo