

LED line PRIME

Code: 204539-DALI

EAN: 5905378220041

Panel Backlit 34W CCT 4760lm UGR<19
62x62 DALI PRIME



The 34W PRIME LED line panel is a perfect light source that emits a light stream of 4,760 lumens. It is characterized by a Ra 80 colour reproduction factor and a low UGR value (<19), which provides comfortable space lighting. The choice of light colour temperature in the ranges 3000 K, 4000 K and 5000 K allows to adjust the atmosphere of the room according to the needs.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	<ul style="list-style-type: none">34 W
Voltage	<ul style="list-style-type: none">220-240 V AC
Correlated colour temperature	<ul style="list-style-type: none">3000 K4000 K5000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	140
Luminous flux	4760
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	Triac
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	90
LED type	SMD LED 2835
LED quantity	128
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Colour	White
Material (housing)	Aluminium
Material (cover)	Polystyrene

LED line PRIME

Code: 204539-DALI

EAN: 5905378220041

**Panel Backlit 34W CCT 4760lm UGR<19
62x62 DALI PRIME**

Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 204539-DALI

EAN: 5905378220041

**Panel Backlit 34W CCT 4760lm UGR<19
62x62 DALI PRIME**

Example application