

LED line PRIME

Code: 249433

EAN: 5901583249433

**LED strip 300/5m SMD 12V 6500K 4,8W
IP20 8mm 30m 400lm/m PRIME**



LED strip 300 SMD 12V 6500K 4.8W 30m from PRIME LED line is an advanced lighting solution that provides bright, white light with a colour temperature of 6500K. High light efficiency of 83 lm/W and power of only 4.8 W/m provide G-class energy efficiency. Thanks to the use of SMD3528 diodes and PWM technology, smooth dimming is possible.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	G
Warranty	5
Power	• 4.8 W / m
Voltage	• 12 V DC
Correlated colour temperature	• 6500 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	III
Cutting section	5 cm
Luminous efficacy	83
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h
Survival factor	0.9
Dimmable function	PWM

Parameter	Value
Colour consistency in McAdam ellipses	≤3
Luminous flux (lm)	400
Current (Im)	0,4
Beam angle	120
LED type	SMD3528
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (lm)	60
Type of adhesive tape	3M 300 LSE
Lifespan	100 000 h
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
Height	2,5


LED line PRIME

Code: 249433


EAN: 5901583249433

**LED strip 300/5m SMD 12V 6500K 4,8W
IP20 8mm 30m 400lm/m PRIME**

Technical drawing






Light distribution



Additional product photos

Logistics data



Single packaging

Quantity	30 m
Width	380 mm
Height	130 mm
Length	400 mm
Weight	0,522 kg

Bulk packaging

Quantity	20
Width	450 mm
Height	290 mm
Length	350 mm
Volume	0,045 m3
Weight	11 kg
Comments	

Europallet

Quantity	14400 m
Height	1740 mm
Quantity in layer	80
Number of layers	6
Bulk quantity	480
Weight	223 kg

LED line PRIME

Code: 249433

EAN: 5901583249433

**LED strip 300/5m SMD 12V 6500K 4,8W
IP20 8mm 30m 400lm/m PRIME**

Example application