


LED line LITE

Code: 475565

EAN: 5907777475565

LED line LITE Outdoor wall mounted luminaire LED 2x3W 4000K IP54 gray CILINDER



Technical data

Parameter	Value
Colour of the light	White
Energy efficiency class 2019/2015	G
Colour consistency in McAdam ellipses	≤6
IP protection rating	IP54
Warranty (years)	3
Survival factor	0.9
Lifetime L70B50	30 000
Dimensions (L. x W x H.)	13,5x11,5x10cm
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
The lumen maintenance factor	96 %
Beam angle	0-120 °
Material (cover)	glass
Material (housing)	aluminum

Parameter	Value
LED type	2835 SMD
LED quantity	14
Lifespan	30000
Power Factor	0,5
Number of on/off cycles	20000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor and outdoor use	YES
IEC protection class	II
IK protection rating	05
Power	• 6 W
Voltage	• 100-260 V AC
Correlated colour temperature	• 4000 K

LED line LITE

Code: 475565


EAN: 5907777475565

LED line LITE Outdoor wall mounted luminaire LED 2x3W 4000K IP54 gray CILINDER




Dimensions

Light distribution

Additional product photos



Logistics data



Single packaging

Width	110 mm
Height	110 mm mm
Length	110 mm mm
Weight	0,35 kg kg
	1

Bulk packaging

Number of pieces/tape in meters pack zb	40 szt.
Width	640 mm mm
Height of collective packaging	460 mm
Length	310 mm mm
Weight	14,35 kg kg
Volume	0,091 m3 m3

Europallet

Number of pieces/tapes in meters euro pallet	840
Quantity collective euro pallet	480 szt.
Weight of a euro pallet	172,2 kg kg
Pallet height	1840 mm
Quantity in 1 layer	120 szt.
Number of layers	4

LED line LITE

Code: 475565

EAN: 5907777475565

**LED line LITE Outdoor wall mounted
luminaire LED 2x3W 4000K IP54 gray
CILINDER**

Example application