

LED line PRIME

Code: 200203

EAN: 5905378200203

LED line PRIME Floodlight 30W 4000K
4200lm 120°



The PRIME Floodlight 30W LED line is an advanced lighting solution with high energy efficiency of 140 lm/W. It emits a luminous flux of 4,200 lumens at a colour temperature of 4000 K. IP66 leak class guarantees resistance to difficult weather conditions, making it ideal for external applications.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 30 W
Voltage	• 100-227 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	08
IEC protection class	I
Luminous efficacy	140
Luminous flux	4200
The lumen maintenance factor	96
Lifetime L70B50	50 000 h

Parameter	Value
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Wire length	890 mm
Mounting type	surface
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2835
LED quantity	96
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-40÷45
Material (housing)	Aluminium
Material (cover)	tempered glass


LED line PRIME

Code: 200203


EAN: 5905378200203

**LED line PRIME Floodlight 30W 4000K
4200lm 120°**

Technical drawing




Light distribution




Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 200203

EAN: 5905378200203

**LED line PRIME Floodlight 30W 4000K
4200lm 120°**

Example application