

LED line LITE

Code: 200777

EAN: 5905378200777

**DOWNLIGHT MOLLY 3000K 12W 1150lm
round IP20 White LITE**



LED line LITE Downlight MOLLY with 12W power and 1150 lm light stream in 3000K is an ideal solution for demanding users. It is characterized by high light efficiency, up to 95 lm/W and Ra > 80 colour reproduction, which provides a natural lighting effect. It has IP20 leak class and excellent service life of 30,000 hours.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	3
Power	• 12 W
Voltage	• 170-260 V AC
Correlated colour temperature	• 3000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	II
Luminous efficacy	95
Luminous flux	1150
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	110
LED type	SMD LED 2835
LED quantity	45
Power Factor	0,5
Number of on/off cycles	50000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Mounting hole diameter	120-135
Height	26
Fixture's diameter	145 mm
Colour	White
Material (housing)	Polycarbonate


LED line LITE

Code: 200777


EAN: 5905378200777

**DOWNLIGHT MOLLY 3000K 12W 1150lm
round IP20 White LITE**

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	152 mm
Height	35 mm
Length	148 mm
Weight	0,143 kg

Bulk packaging

Quantity	60
Width	390 mm
Height	322 mm
Length	473 mm
Volume	0,043 m3
Weight	8,58 kg

Europallet

Quantity	1800
Height	1,7 m
Quantity in layer	360
Number of layers	5
Bulk quantity	30
Weight	288 kg

LED line LITE

Code: 200777

EAN: 5905378200777

**DOWNLIGHT MOLLY 3000K 12W 1150lm
round IP20 White LITE**

Example application

