


**LED line® E14 7W 2700K 630lm 170-250V G50**

The structural design of this product ensures effective heat dissipation.



Manufacturer issues a 3-year warranty for this product.



Voltage range and voltage type



LED type



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Beam angle



Ambient temperature suitable for operation




Lifespan

Parameter	Value
Luminous efficacy	90 lm/W
Power	7 W
Colour of the light	White
Energy efficiency class 2019/2015	F
Luminous flux	630 lm
Correlated colour temperature	2700 K
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
Survival factor	0.9
Lifetime L70B50	30 000
Supply voltage range and voltage type	170-250 VAC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80

Parameter	Value
Beam angle	280 °
Material (housing)	Ceramic
LED type	SMD2835
Lifespan	30000
Power Factor	0,5
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-5÷40 °C
For indoor use	Inside
Full box quantity	100 pc
Lamp's warm-up time to 60%	1
Height	102 mm
Product weight with packaging	72 g

The lumen maintenance factor	96 %	Master carton weight (kg)	7,2
Lamp's diameter	50	Energy class	A+



**Single packaging**




Width	55 mm
Height	115 mm
Length	55 mm
Weight	0,6 kg
	1

**Bulk packaging**



Width	100
	295 mm
Length	250
	575 mm
Weight	8 kg
Volume	0,042406 m3

**Europallet**



Weight of a euro pallet	24
	168 kg
	1644
	4
	6