


LED line LITE Code: 202887 EAN: 5905378202887

LED line LITE Panel Backlit 40W 4000K 4000Im 595x595



















Technical data

Parameter	Value
Voltage	• 220-240 V AC
Luminous efficacy	100
Colour of the light	White
Energy efficiency class 2019/2015	F
Luminous flux	4000
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
IP protection rating	IP20
Dimmable function	PWM
Survival factor	0.9
Lifetime L70B50	30 000 h
Working current	0,193
Dimmable	NO
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	white

Parameter	Value
The lumen maintenance factor	96
Beam angle	120
Material (cover)	polystyrene
Material (housing)	Aluminium
LED type	SMD LED 2835
LED quantity	48
Power Factor	0,9
Number of on/off cycles	25000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-25÷45
For indoor use	Inside
IEC protection class	1
IK protection rating	02
Lamp's warm-up time to 60%	ls
Correlated colour temperature	• 4000 K
Power	• 40 W




LED line LITE Code: 202887 EAN: 5905378202887

LED line LITE Panel Backlit 40W 4000K 4000lm 595x595


Technical drawing

Light distribution

Luminous [cd/klm]




Additional product photos









Logistics data







Single packaging

Bulk packaging

Europallet



LED line LITE Code: 202887 EAN: 5905378202887

LED line LITE Panel Backlit 40W 4000K 4000lm 595x595

Example application

