

LED line PRIME


Code: 201057-AW3HAT

EAN: 5905378212206

LINKER TRI-PROOF 80W 4000K  
12000lm 150lm/W 220-240V IP65 150cm  
Emergency module 3H AT PRIME



Linker 80W from LED line PRIME is a modern and efficient light source, offering a brightness of 12000 lumens, which provides excellent lighting in all conditions. Light performance of 150 lm/W and colour temperature 4000 K guarantee natural color reproduction. IP65 leak class provides resistance to water and dust, and emergency mode time up to 3 hours increases safety.



Technical data

Parameter	Value
Operating time in emergency mode	3 h
Emergency module test	Autotest
ULOR	3 %
Voltage	• 220-240 V AC
Luminous efficacy	150
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	12000
Colour consistency in McAdam ellipses	≤6
Warranty (years)	5
Dimmable function	PWM
Survival factor	0.9
Lifetime L70B50	100 000 h
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80

Parameter	Value
Colour	Grey
The lumen maintenance factor	96
Beam angle	120
Material (cover)	polycarbonate
Material (housing)	Polycarbonate
Lifespan	100 000 h
Power Factor	0,95
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-25 ÷ 45
IEC protection class	II
Lamp's warm-up time to 60%	1 s
Correlated colour temperature	• 4000 K
Power	• 80 W

LED line PRIME

Code: 201057-AW3HAT

EAN: 5905378212206

**LINKER TRI-PROOF 80W 4000K  
12000lm 150lm/W 220-240V IP65 150cm  
Emergency module 3H AT PRIME**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

---

LED line PRIME

Code: 201057-AW3HAT

EAN: 5905378212206

**LINKER TRI-PROOF 80W 4000K  
12000lm 150lm/W 220-240V IP65 150cm  
Emergency module 3H AT PRIME**

---

**Example application**