

LED line LITE

Code: 203549

EAN: 5905378203549

LED line LITE Floodlight PHOTON 50W
4000K 5000lm



product_card.label_technical_data

Parameter	Value	Parameter	Value
ULOR	0 %	Material (cover)	tempered glass
Luminous efficacy	100 lm/W	Material (housing)	DIE-CAST alu
Colour of the light	White	LED type	SMD2835
Energy efficiency class 2019/2015	F	LED quantity	75
Luminous flux	5000 lm	Power Factor	0,9
Colour consistency in McAdam ellipses	≤6	Number of on/off cycles	18000
IP protection rating	IP65	Colour consistency in McAdam ellipses	≤6
Warranty (years)	3	Ambient temperature suitable for operation	-20÷40 °C
Survival factor	0.9	For indoor and outdoor use	YES
Lifetime L70B50	30 000	IEC protection class	I
Rated power	220-240V AC	IK protection rating	05
Weight	530 g	Lamp's warm-up time to 60%	1
Mounting type	surface	Length	191 mm
Frequency of the supply voltage	50/60Hz	Width	32 mm
Colour rendering index Ra	80	Height	210 mm
Colour	Black	Power	• 50 W
The lumen maintenance factor	96 %	Voltage	• 220-240 V AC
Beam angle	120 °	Correlated colour temperature	• 4000 K

LED line LITE

Code: 203549


EAN: 5905378203549

LED line LITE Floodlight PHOTON 50W
4000K 5000lm


product_card.label_dimensions

product_card.label_curve_light

product_card.label_product_gallery




product_card.label_logistic_data




Single packaging

Width	191 mm
Height	210 mm mm
Length	32 mm mm
Weight	0,53 kg kg
	1



Bulk packaging

Number of pieces/tape in meters pack zb	12 szt.
Width	417 mm mm
Height of collective packaging	191 mm
Length	278 mm mm
Weight	6,71 kg
Volume	0,022 m3 m3



Europallet

Quantity collective euro pallet	480 szt.
Weight of a euro pallet	268,4 kg
Pallet height	1910 mm
Quantity in 1 layer	48 szt.
Number of layers	10

LED line LITE

Code: 203549

EAN: 5905378203549

LED line LITE Floodlight PHOTON 50W
4000K 5000lm

Example application