

LED line LITE

Code: 202320

EAN: 5905378202320

**LED bulb E27 2700K 7W 840lm 230V
360° FILAMENT A60 DIM Glass LITE**



LED bulb E27 7W 2700K 840lm FILAMENT A60 DIM from LED line LITE is an advanced light source that combines style with modernity. It emits a warm, white light with a colour temperature of 2700 K and a high light stream of 840 lumens. Its life span is up to 25,000 hours, and the number of incorporation cycles is as much as 50,000. Thanks to the brightness control function and energy efficiency class E, the bulb provides flexibility and energy savings.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 7 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 2700 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
Luminous efficacy	120
Luminous flux	840 lm
The lumen maintenance factor	96
Lifetime L70B50	25 000 h
Survival factor	0.9
Dimmable function	Triac
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Lamp's type	A60
Beam angle	360 °
LED type	Filament
LED quantity	4
Lifespan	25 000 h
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	108
Fixture's diameter	60 mm
Material	Glass
Material (housing)	Glass
Material (cover)	glass


LED line LITE

Code: 202320

EAN: 5905378202320

**LED bulb E27 2700K 7W 840lm 230V
360° FILAMENT A60 DIM Glass LITE**

Technical drawing






Light distribution

Additional product photos



Logistics data



Single packaging

Quantity	1
Width	50 mm
Height	59 mm
Length	50 mm
Weight	0,03 kg

Bulk packaging

Quantity	50
Width	325 mm
Height	240 mm
Length	325 mm
Volume	0,025 m ³
Weight	2,78 kg

Europallet

Height	1920 mm
Quantity in layer	300
Number of layers	8
Bulk quantity	2400
Weight	133,44 kg

LED line LITE

Code: 202320

EAN: 5905378202320

**LED bulb E27 2700K 7W 840lm 230V
360° FILAMENT A60 DIM Glass LITE**

Example application

