

LED line PRIME LED bulb E27 10W 6500K 1400lm 170-250V A60



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Manufacturer issues a 5-year warranty for this product.



70-250 VAC

Voltage range and voltage type



Lamp type



Lifespan



The structural design of this product ensures effective heat dissipation.



Beam angle



MAX
-20+40 °C

Ambient temperature suitable for operation



LED type

Parameter	Value
Luminous efficacy	140 lm/W
Power	10 W
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	1400 lm
Correlated colour temperature	6500 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	20
Warranty (years)	5
Dimmable function	PWM
Survival factor	0.9
Lifetime L70B50	30 000
Material	Ceramic
Supply voltage range and voltage type	170-250 VAC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White

Parameter	Value
The lumen maintenance factor	96 %
Lamp's type	A60
Lamp's diameter	60
Beam angle	280 °
Material (cover)	glass
Material (housing)	Ceramic
LED type	SMD2835
Lifespan	30000
Power Factor	0,5
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
Full box quantity	100 pc
Lamp's warm-up time to 60%	1
Height	110 mm
Master carton weight (kg)	8

Single packaging




Width	65 mm
Height	150 mm
Length	65 mm
Weight	0,06 kg
	1

Bulk packaging



Number of pieces/tape in meters pack zb	100 szt.
Width	665 mm
Height of collective packaging	275 mm
Length	340 mm
Weight	7,5 kg
Volume	0,062 m ³

Europallet



Quantity collective euro pallet	2100 szt.
Weight of a euro pallet	157,5 kg
Pallet height	1925 mm
Quantity in 1 layer	300 szt.
Number of layers	7