

LED line PRIME

Code: 202450

EAN: 5905378202450

**FLOODLIGHT 4000K 100W 14000lm T2
IP66 PRIME**



The 100W PRIME Floodlight LED line provides an impressive light stream of 14,000 lumens with an energy efficiency of 140 lm/W. Thanks to the IP66 seal class, it is resistant to adverse weather conditions, which allows its use both inside and outside. High durability of components and long life of LEDs up to 50,000 hours guarantee reliability and low operating costs.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5/7*
Power	• 100 W
Voltage	• 100-277 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	08
IEC protection class	I
Luminous efficacy	140
Luminous flux	14000
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h

Parameter	Value
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Wire length	920 mm
Mounting type	surface
Frequency of the supply voltage	50/60Hz
Beam angle	70°155
LED type	SMD2835
LED quantity	216
Power Factor	0.9
Number of on/off cycles	50000
Ambient temperature suitable for operation	-40÷45
Height	46 mm
Material (housing)	Aluminium
Material (cover)	Tempered glass


LED line PRIME

Code: 202450


EAN: 5905378202450

**FLOODLIGHT 4000K 100W 14000lm T2
IP66 PRIME**

Technical drawing




Light distribution



Additional product photos



Logistics data



Single packaging

Width	330 mm
Height	47,5 mm
Length	268 mm
Weight	1,85 kg

Bulk packaging

Quantity	5
Width	395 mm
Height	305 mm
Length	300 mm
Volume	0,036 m3
Weight	9,6 kg
Comments	

Europallet

Quantity	200
Height	1830 mm
Quantity in layer	40
Number of layers	6
Bulk quantity	240
Weight	460,8 kg

LED line PRIME

Code: 202450

EAN: 5905378202450

**FLOODLIGHT 4000K 100W 14000lm T2
IP66 PRIME**

Example application