

LEDOM Outdoor wall mounted luminaire LED 2x3W 4000K IP54 gray CUBE



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Manufacturer issues a 3-year warranty for this product.



Voltage range and voltage type



Ambient temperature suitable for operation



Lifespan



This product is suitable for surface-mounted installation.



Beam angle



LED type




LED quantity

Parameter	Value
Energy efficiency class 2019/2015	G
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	54
Warranty (years)	3
Dimmable function	No
Survival factor	30000
Lifetime L70B50	30 000
Dimensions (L. x W x H.)	10x10x10cm
Supply voltage range and voltage type	100- 260V AC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	Gray
The lumen maintenance factor	96
Beam angle	0-120 °
Material (cover)	glass
Material (housing)	Polycarbonate
LED type	2835 SMD
LED quantity	14
Lifespan	30000


Parameter	Value
Power Factor	0,5
Number of on/off cycles	20000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20 ÷ 40 °C
For indoor and outdoor use	YES
IK protection rating	05
EPREL ID	1 078 031
Form of the product (EPREL)	Source Out
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
Is the product equipped with an integrated light source? (EPREL)	Yes
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	No
Mains or non- mains light source (EPREL)	MLS
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
R9 colour rendering index value (EPREL)	0
Total luminous flux (EPREL)	490
On-mode power P _{on} (EPREL)	6
Useful luminous flux Φ _{use} (EPREL)	490
Beam angle in degrees (EPREL)	120

Single packaging




110
110
110
0,3
1

Bulk packaging



40

Europallet



6