

LED line LITE

Code: 243929

EAN: 5901583243929

**LED bulb G4 3000K 2W 140lm 12V
AC/DC 120° LITE**



LED line LITE G4 2W 3000K 140lm is an energy-efficient LED bulb that is characterized by a light stream of 140 lumens at 2W power. It emits a warm, white light with a colour temperature of 3000 K, ideal for creating a cozy atmosphere. Thanks to the high colour rendering coefficient $Ra \geq 80$ and a wide light angle of 120°, it provides natural color reproduction and uniform light scattering. The lifetime of the product is as much as 50,000 hours.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	G
Warranty	3
Power	• 2 W
Voltage	• 12 V AC/DC
Correlated colour temperature	• 3000 K
Colour of the light	White
Colour rendering index Ra	80
Luminous efficacy	70
Luminous flux	140 lm
The lumen maintenance factor	96
Lifetime L70B50	50 000 h

Parameter	Value
L80B* – difference B10–B50 \approx 1% (according to LightingEurope) – negligible	35000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤ 6
Frequency of the supply voltage	50/60Hz
Beam angle	120°
Lifespan	50 000 h
Number of on/off cycles	50000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	30
Fixture's diameter	19 mm

LED line LITE

Code: 243929

EAN: 5901583243929




**LED bulb G4 3000K 2W 140lm 12V
AC/DC 120° LITE**

Technical drawing

Light distribution

Additional product photos

Logistics data



Single packaging

Quantity	1
Width	30 mm
Height	9 mm
Length	42 mm
Weight	0,002 kg

Bulk packaging

Quantity	1000
Width	610 mm
Height	235 mm
Length	150 mm
Volume	0,021 m ³
Weight	3,88 kg
Comments	

Europallet

Quantity	54000
Height	1880 mm
Quantity in layer	8000
Number of layers	8
Bulk quantity	64000
Weight	248,32 kg

LED line LITE

Code: 243929

EAN: 5901583243929

**LED bulb G4 3000K 2W 140lm 12V
AC/DC 120° LITE**

Example application