


LED line LITE G4 2W 3000K 140lm 12V AC/DC 12 SMD2835



Beam angle



Ambient temperature suitable for operation



Voltage range and voltage type




Lifespan

Parameter	Value
Luminous efficacy	70 lm/W
Power	2 W
Colour of the light	White
Energy efficiency class 2019/2015	G
Luminous flux	140 lm
Correlated colour temperature	3000 K
Colour consistency in McAdam ellipses	≤6
Warranty (years)	2
Survival factor	0.9
Lifetime L70B50	50 000
Supply voltage range and voltage type	12V AC/DC
Frequency of the supply voltage	50/60Hz


Parameter	Value
Colour rendering index Ra	80
The lumen maintenance factor	96 %
Lamp's diameter	19
Beam angle	120 °
Lifespan	50000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
Height	30 mm
Product weight with packaging	3 g
Energy class	A+

Single packaging




Width	30 mm
Height	9 mm
Length	42 mm
Weight	0,002 kg
	1

Bulk packaging



Number of pieces/tape in meters pack	1000 szt.
Width	610 mm
Height of collective packaging	235 mm
Length	150 mm
Weight	3,88 kg
Volume	0,021 m ³

Europallet



Number of pieces/tapes in meters euro pallet	54000 szt.
Quantity collective euro pallet	64000 szt.
Weight of a euro pallet	248,32 kg
Pallet height	1880 mm
Quantity in 1 layer	8000 szt.
Number of layers	8