

LED line PRIME LED Bulb MR11 3W 6500K 330lm 10-14V AC/DC 38°



Manufacturer issues a 5-year warranty for this product.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Voltage range and voltage type



Lamp type



Lifespan



The structural design of this product ensures effective heat dissipation.



Beam angle



Ambient temperature suitable for operation




LED type

Parameter	Value
Luminous efficacy	110 lm/W
Power	3 W
Colour of the light	White
Energy efficiency class 2019/2015	F
Luminous flux	330 lm
Correlated colour temperature	6500 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	20
Warranty (years)	5
Survival factor	0.9
Lifetime L70B50	30 000
Material	Ceramic
Supply voltage range and voltage type	10-14V AC/DC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White

Parameter	Value
The lumen maintenance factor	96 %
Lamp's type	MR11
Lamp's diameter	35
Beam angle	38 °
Material (housing)	Ceramic
LED type	SMD2835
Lifespan	30000
Power Factor	0,5
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-5+40 °C
For indoor use	Inside
Full box quantity	100 pc
Lamp's warm-up time to 60%	1
Height	35 mm
Master carton weight (kg)	4

Single packaging



Width	47 mm
Height	125 mm
Length	47 mm
Weight	0,03 kg
	1

Bulk packaging



Number of pieces/tape in meters pack zb	100 szt.
Width	420 mm
Height of collective packaging	115 mm
Length	205 mm
Weight	5 kg
Volume	0,009 m ³

Europallet



Quantity collective euro pallet	9600 szt.
Weight of a euro pallet	480 kg
Pallet height	1840 mm
Quantity in 1 layer	600 szt.
Number of layers	16