

LED line PRIME

Code: 200340

EAN: 5905378200340

LED line PRIME Floodlight 100W 4000K
14000lm 90°

ATTENTION



Technical data

Parameter	Value	Parameter	Value
Luminous efficacy	140 lm/W	LED type	SMD2835
Colour of the light	White	LED quantity	216
Energy efficiency class 2019/2015	D	Power Factor	0,9
Luminous flux	14000 lm	Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6	Colour consistency in McAdam ellipses	≤6
IP protection rating	IP66	Ambient temperature suitable for operation	-40÷45 °C
Warranty (years)	5	For indoor and outdoor use	YES
Survival factor	0.9	IEC protection class	I
Lifetime L70B50	50 000	IK protection rating	08
Wire length	920 mm	Full box quantity	5 pc
Weight	2,1 g	Lamp's warm-up time to 60%	1
Mounting type	surface	Length	330 mm
Frequency of the supply voltage	50/60Hz	Width	268 mm
Colour rendering index Ra	70	Height	47,5 mm
The lumen maintenance factor	96 %	Power	• 100 W
Beam angle	90 °	Voltage	• 100-227 V AC
Material (cover)	tempered glass	Correlated colour temperature	• 4000 K
Material (housing)	aluminum		

LED line PRIME

Code: 200340


EAN: 5905378200340

LED line PRIME Floodlight 100W 4000K
14000lm 90°


Dimensions

Light distribution

Additional product photos




Logistics data




Single packaging

Width	330 mm
Height	58 mm mm
Length	268 mm mm
Weight	1,85 kg kg



Bulk packaging

Number of pieces/tape in meters pack zb	5 szt.
Width	3950 mm mm
Height of collective packaging	3050 mm
Length	50 mm mm
Weight	9,6 kg kg
Volume	0,602 m3 m3



Europallet

Number of pieces/tapes in meters euro pallet	200
Quantity collective euro pallet	240
Weight of a euro pallet	485,8 kg kg
Pallet height	183 cm
Quantity in 1 layer	40
Number of layers	6

LED line PRIME

Code: 200340

EAN: 5905378200340

**LED line PRIME Floodlight 100W 4000K
14000lm 90°**

Example application