

LED line PRIME

Code: 204218

EAN: 5905378204218

LED line PRIME FUSION linear lamp
40W 4000K 5200lm 0-10V P18° white



FUSION 40W linear housing from PRIME LED line is a perfect solution for demanding spaces. It emits light with a colour temperature of 4000 K, generating a luminous flux of 5200 lm at 130 lm/W. The angle of light distribution is 120°, which provides even lighting. The integrated 0-10V dimming function allows you to adjust the intensity of the lighting.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 40 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	08
IEC protection class	I
Luminous efficacy	130
Luminous flux	5200
The lumen maintenance factor	96

Parameter	Value
Lifetime L70B50	50 000 h
Survival factor	0.9
Dimmable function	0-10
Colour consistency in McAdam ellipses	≤6
Sling length	200 cm
Standby power	0
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Power Factor	0,9
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside

LED line PRIME

Code: 204218


EAN: 5905378204218

**LED line PRIME FUSION linear lamp
40W 4000K 5200lm 0-10V P18° white**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 204218

EAN: 5905378204218

**LED line PRIME FUSION linear lamp
40W 4000K 5200lm 0-10V P18° white**

Example application