

LED line PRIME Code: 204164 EAN: 5905378204164

LED line PRIME FUSION linear lamp 40W 4000K 5200lm 0-10V 30*90° white



FUSION 40W 4000K linear mounting from PRIME LED line is an excellent solution for demanding users. It offers a luminous flux of 5,200 lumens, with a high light output of 130 lm/W. Thanks to the 0-10V dimming function and the 0.9 PF power factor, the setting adapts perfectly to different lighting conditions.

















Parameter

Technical data

Parameter	Value
Energy efficiency class 2019/2015	С
Warranty	5
Power	• 40 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	08
IEC protection class	1
Luminous efficacy	130
Luminous flux	5200
The lumen maintenance factor	96

raidiffecei	varac
Lifetime L70B50	50 000 h
Survival factor	0.9
Dimmable function	0-10
Colour consistency in McAdam ellipses	≤6
Sling length	200 cm
Standby power	0
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside

Value



LED line PRIME Code: 204164 EAN: 5905378204164

LED line PRIME FUSION linear lamp 40W 4000K 5200lm 0-10V 30*90° white

Technical drawing

Light distribution


70 1158 %I [[______


Additional product photos






Logistics data







Single packaging

Bulk packaging

Europallet

MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME Code: 204164 EAN: 5905378204164

LED line PRIME FUSION linear lamp 40W 4000K 5200lm 0-10V 30*90° white

Example application