

LED line PRIME

Code: 479587-AW1HAT

EAN: 5905378218208

LINKER TRI-PROOF 21W 4000K 3150lm  
150lm/W IP65 60cm Emergency module  
1H AT PRIME



LINKER 21W 4000K is a modern LED module with a power of 21 W, offering an impressive light stream of 3150 lm, which translates into efficiency 150 lm/W. Its light colour is 4000 K, providing neutral lighting. The product is characterized by high IP65 tightness, making it resistant to atmospheric conditions. The emergency module with self-test function guarantees reliability in emergency situations, providing up to one hour of work.



Technical data

Parameter	Value
Operating time in emergency mode	1 h
Emergency module test	Autotest
ULOR	3 %
Voltage	• 220-240 V AC
Luminous efficacy	150
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	3150
Colour consistency in McAdam ellipses	≤6
Warranty (years)	5
Dimmable function	PWM
Survival factor	0.9
Lifetime L70B50	100 000 h
Frequency of the supply voltage	50/60Hz

Parameter	Value
Colour rendering index Ra	80
Colour	Grey
The lumen maintenance factor	96
Beam angle	120
Material (cover)	polycarbonate
Material (housing)	Polycarbonate
Lifespan	100 000 h
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-25 ÷ 45
IEC protection class	II
Lamp's warm-up time to 60%	1 s
Correlated colour temperature	• 4000 K
Power	• 21 W

LED line PRIME

Code: 479587-AW1HAT

EAN: 5905378218208


**LINKER TRI-PROOF 21W 4000K 3150lm  
150lm/W IP65 60cm Emergency module  
1H AT PRIME**

Technical drawing


Light distribution

Additional product photos


Logistics data



Single packaging



Bulk packaging



Europallet

---

LED line PRIME

Code: 479587-AW1HAT

EAN: 5905378218208

**LINKER TRI-PROOF 21W 4000K 3150lm  
150lm/W IP65 60cm Emergency module  
1H AT PRIME**

---

**Example application**