


LED line® strip 300 SMD 12V blue 4,8W IP65



LED Strip line is a modern and versatile linear **light source**, used for interior lighting, furniture, lightboxes, illuminated signs, and public spaces.



Yellow free technology means that the housing of this product is made of high quality material which is resistant to yellowing degeneration caused by UV radiation, thanks to which the product maintains its esthetic appearance for many years.



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



This product is featured by a high degree of IP protection, which makes it suitable for a broader range of lighting applications and offers high safety of use.



Manufacturer issues a 3-year warranty for this product.



Beam angle



Voltage range and voltage type



Ambient temperature suitable for operation



LED type



Lifespan



LED quantity (1m)




Dimmable

Parameter	Value
Colour of the light	Blue
Warranty (years)	3
Dimmable function	PWM
Minimum purchase quantity	5
Lifetime L70B50	30 000
Wattage (1m)	4,8 W
Current (1m)	0,4
Supply voltage range and voltage type	12 VDC
Metres per roll	5
The lumen maintenance factor	>0,7 %
Beam angle	120 °
LED type	SMD3528
Not dimmable	TAK
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2

Parameter	Value
LED quantity (1m)	60
Cutting section	5
Type of adhesive tape	3M 300 LSE
Lifespan	100000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤3
Ambient temperature suitable for operation	-20÷45 °C
For indoor and outdoor use	YES
IEC protection class	III
Full box quantity	75 pc
Lamp's warm-up time to 60%	1
Width	8 mm
Height	3 mm
Product weight with packaging	192 g
Master carton weight (kg)	14,4

Luminous [cd/klm]




C0 - C180 C90 - C270

Single packaging



1

Bulk packaging



Width	100 340 mm
Length	280 440 mm
Weight	0,18 kg
Volume	0,042 m ³

Europallet



Weight of a euro pallet	60 300 kg
	1800
	6
	10