

LED line LITE

Code: 241918

EAN: 5901583241918

LED line® GU10 3W 4000K 273lm 220-260V 120°



Technical data

Parameter	Value
Luminous efficacy	91 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	F
Luminous flux	273 lm
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
Survival factor	0.9
Lifetime L70B50	30 000
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
The lumen maintenance factor	96 %
Lamp's diameter	50
Beam angle	120 °
Material (cover)	glass
Material (housing)	Glass

Parameter	Value
LED type	SMD2835
Lifespan	30000
Power Factor	0,4
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
Full box quantity	100 pc
Lamp's warm-up time to 60%	1
Height	55 mm
Energy class	A++
Power	• 3 W
Voltage	• 220-260 V AC
Correlated colour temperature	• 4000 K

LED line LITE


Code: 241918

EAN: 5901583241918


LED line® GU10 3W 4000K 273lm 220-260V 120°

Dimensions




Light distribution



Additional product photos



Logistics data



Single packaging

Width	50 mm
Height	50 mm mm
Length	60 mm mm
Weight	0,07 kg kg
	10

Bulk packaging

Number of pieces/tape in meters pack zb	100 szt.
Width	595 mm mm
Height of collective packaging	170 mm
Length	290 mm mm
Weight	6,5 kg kg
Volume	0,029 m3 m3

Europallet

Number of pieces/tapes in meters euro pallet	4500
Quantity collective euro pallet	4400 szt.
Weight of a euro pallet	286 kg kg
Pallet height	1870 mm
Quantity in 1 layer	400 szt.
Number of layers	11

LED line LITE

Code: 241918

EAN: 5901583241918

**LED line® GU10 3W 4000K 273lm 220-
260V 120°**

Example application