

LED line LITE

Code: 247286

EAN: 5901583247286

LED line SMD 5W 2700K 400lm 220-260V 50mm



product_card.label_technical_data

Parameter	Value
Luminous efficacy	80 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	G
Luminous flux	400 lm
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
Survival factor	0.9
Lifetime L70B50	30 000
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	white
The lumen maintenance factor	96 %
Lamp's diameter	50
Beam angle	110 °
Material (cover)	glass

Parameter	Value
Material (housing)	Ceramic
LED type	SMD2835
Lifespan	30000
Power Factor	0,4
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
Full box quantity	100 pc
Lamp's warm-up time to 60%	1
Height	22 mm
Energy class	A+
Power	• 5 W
Voltage	• 220-260 V AC
Correlated colour temperature	• 2700 K


LED line LITE

Code: 247286


EAN: 5901583247286

LED line SMD 5W 2700K 400lm 220-260V 50mm

product_card.label_dimensions




product_card.label_curve_light




product_card.label_product_gallery

product_card.label_logistic_data




Single packaging

Width	50 mm
Height	50 mm mm
Length	60 mm mm
Weight	0,08 kg kg
	10



Bulk packaging

Number of pieces/tape in meters pack zb	100 szt.
Width	595 mm mm
Height of collective packaging	170 mm
Length	290 mm mm
Weight	7 kg kg
Volume	0,029 m3 m3



Europallet

Number of pieces/tapes in meters euro pallet	4500
Quantity collective euro pallet	4400 szt.
Weight of a euro pallet	308 kg kg
Pallet height	1870 mm
Quantity in 1 layer	400 szt.
Number of layers	11

LED line LITE

Code: 247286

EAN: 5901583247286

LED line SMD 5W 2700K 400lm 220-260V 50mm

Example application