LED line PRIME

Code: 228078-DALI

EAN: 5905378232235

Downlight CALMOS PRO 5CCT (2.7/3/4/5/6K) 18/23W 2760lm 60° round IP65 White UGR<19 PRIME DALI



New

The Calmos 5CCT PRO downlight by LED line is an innovative and economical solution for professional applications, offering five color temperatures and two power levels in one fixture. Thanks to the recessed light source, you gain high visual comfort without glare (UGR<19) and a precise beam angle of 60 degrees. Four different sizes and a reliable external power supply make it easy to adapt the lighting to any project, and the 5-year warranty will give you complete peace of mind. It’s the perfect way to reduce inventory and maximize work flexibility for the installer.

IP 65 | IK 06 | 220-240V AC

Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	5
Power	• 18 W • 23 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 2700 K • 3000 K • 4000 K • 5000 K • 6000 K
Colour of the light	CCT
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	06
IEC protection class	II
Luminous efficacy	120

Parameter	Value
Luminous flux	2760
Lifetime L70B50	50 000 h
Frequency of the supply voltage	50/60Hz
Beam angle	60°
Power Factor	>=0,9
Ambient temperature suitable for operation	` -20 ~45
Mounting hole diameter	Ø 160-190 mm
Height	102 mm
Fixture's diameter	200 mm
Control	DALI
DALI	• YES

T: +48 29 764 77 00 export@ledline.pl **www.ledline.pl/en**

LED line PRIME

Code: 228078-DALI

EAN: 5905378232235

Downlight CALMOS PRO 5CCT (2.7/3/4/5/6K) 18/23W 2760lm 60° round IP65 White UGR<19 PRIME DALI

Technical drawing



Light distribution

Additional product photos









Logistics data



Single packaging

Width	220 mm
Height	120 mm
Length	220 mm
Weight	0,51 kg



Bulk packaging

Quantity	12
Width	460 mm
Height	385 mm
Length	460 mm
Weight	6,12 kg



Europallet

Quantity	192
Height	1,9 m
Bulk quantity	12
Weight	130 kg

T: +48 29 764 77 00 export@ledline.pl **www.ledline.pl/en**

LED line PRIME

Code: 228078-DALI

EAN: 5905378232235

Downlight CALMOS PRO 5CCT (2.7/3/4/5/6K) 18/23W 2760lm 60° round IP65 White UGR<19 PRIME DALI

Example application

T: +48 29 764 77 00 export@ledline.pl **www.ledline.pl/en**