

LED line PRIME Code: 211070 EAN: 5905378211070

LED line PRIME LED strip 320 COB 24V 4000K 5W IP66



New

LED 320 COB 24V 4000K PRIME is a modern lighting solution offering power of 5 W/m. Thanks to the use of COB technology, high light efficiency of 100 lm/W and exceptional colour rendering coefficient Ra is 90, which guarantees natural color reproduction. It is characterized by a high degree of IP66 protection, making it resistant to moisture and dust. The length of the tape is 5 meters, with the possibility of cutting every 5 cm.















Technical data

Parameter	Value
Voltage	• 24 V DC
Luminous efficacy	100
Colour of the light	White
Energy efficiency class 2019/2015	F
Colour consistency in McAdam ellipses	≤ 3
Warranty (years)	5
IP protection rating	IP66
Dimmable function	PWM
Survival factor	0.9
Minimum purchase quantity	5
Lifetime L70B50	50 000 h
Wire length	200 mm
Wattage (lm)	5
Luminous flux (1m)	500
Current (lm)	0,20
Colour rendering index Ra	90

Parameter	Value
Metres per roll	5 m
The lumen maintenance factor	96
Beam angle	180
LED type	COB
LED quantity	1600
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (1m)	320
Cutting section	5 cm
Type of adhesive tape	3M 300 LSE
Colour consistency in McAdam ellipses	≤ 3
Ambient temperature suitable for operation	`-30 ÷ 45
IEC protection class	III
Correlated colour temperature	• 4000 K
Power	• 5W/m




LED line PRIME Code: 211070 EAN: 5905378211070

LED line PRIME LED strip 320 COB 24V 4000K 5W IP66

Technical drawing

Light distribution

Luminous [cd/klm]



Additional product photos












Logistics data







Single packaging

Bulk packaging

Europallet

MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME Code: 211070 EAN: 5905378211070

LED line PRIME LED strip 320 COB 24V 4000K 5W IP66

Example application