

LED line PRIME

Code: 242915

EAN: 5901583242915

LED line downlight round adjustable die cast aluminium white



Technical data

Parameter	Value	Parameter	Value
Maximum suitable lamp power	35	Type of surface suitable for installation	F
IP protection rating	IP20	Distance from illuminated surface	0.5
Warranty (years)	5	Installation method	recessed
Colour	white	Mounting hole diameter	80 mm
Fixture's diameter	92	For indoor and outdoor use	YES
Lamp's diameter	50	IEC protection class	III
Material (housing)	DIE-CAST alu	Full box quantity	100 pc
Y-axis angle regulation	45	Height	30 mm

LED line PRIME

Code: 242915


EAN: 5901583242915

LED line downlight round adjustable die cast aluminium white




Dimensions

Light distribution

Additional product photos



Logistics data



Single packaging

Width	90 mm
Height	90 mm mm
Length	40 mm mm
Weight	0,05 kg kg
	1

Bulk packaging

Number of pieces/tape in meters pack zb	100 szt.
Width	520 mm mm
Height of collective packaging	220 mm
Length	420 mm mm
Weight	8 kg kg
Volume	0,048 m3 m3

Europallet

Number of pieces/tapes in meters euro pallet	2100
Quantity collective euro pallet	1600 szt.
Weight of a euro pallet	128 kg kg
Pallet height	1760 mm
Quantity in 1 layer	200 szt.
Number of layers	8

LED line PRIME

Code: 242915

EAN: 5901583242915

**LED line downlight round adjustable die
cast aluminium white**

Example application