

LED line LITE

Code: 477040

EAN: 5907777477040

LED line strip 600 SMD 12V 4000K 9,6W IP65



product_card.label_technical_data

Parameter	Value
Luminous efficacy	100 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	F
IP protection rating	IP65
Warranty (years)	3
Dimmable function	PWM
Minimum purchase quantity	5
Lifetime L70B50	30 000
Wire length	200 mm
Wattage (1m)	9,6 W
Luminous flux (1m)	960
Current (1m)	0,8
Colour rendering index Ra	80
Metres per roll	5
The lumen maintenance factor	0,96 %
Beam angle	120 °
LED type	SMD 2835

Parameter	Value
LED quantity	600
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (1m)	120
Cutting section	2,5
Type of adhesive tape	3M 300 LSE
Colour consistency in MacAdam ellipses	≤3
Ambient temperature suitable for operation	-20÷45 °C
For indoor and outdoor use	YES
IEC protection class	III
Length	5000 mm
Width	8 mm
Power	• 9.6
Voltage	• 12 V DC
Correlated colour temperature	• 4000 K

LED line LITE


Code: 477040

EAN: 5907777477040



LED line strip 600 SMD 12V 4000K 9,6W
IP65

product_card.label_dimensions


product_card.label_curve_light



product_card.label_product_gallery




product_card.label_logistic_data




Single packaging

Width	180 mm
Height	20 mm
Length	180 mm
Weight	0,2 kg



Bulk packaging

Number of pieces/tape in meters pack zb	40 szt.
Width	360 mm
Height of collective packaging	180 mm
Length	320 mm
Weight	7,66 kg
Volume	0,020 m3



Europallet

Number of pieces/tapes in meters euro pallet	12000 m
Quantity collective euro pallet	2400 szt.
Weight of a euro pallet	484,6 kg
Pallet height	1800 mm
Quantity in 1 layer	240 szt.
Number of layers	10

LED line LITE

Code: 477040

EAN: 5907777477040

**LED line strip 600 SMD 12V 4000K 9,6W
IP65**

Example application