

LED line LITE

Code: 477040

EAN: 5907777477040

**LED strip 600/5m SMD 12V 4000K 9,6W
IP65 8mm 5m 960lm/m LITE**



The 600 SMD 12V 4000K 9.6W IP65 LED line LITE is a modern light source that provides even lighting with SMD 2835 LEDs. It is white with a temperature of 4000K and a light angle of 120 degrees. It offers high light performance of 100 lm/W and a durability of up to 30,000 hours. IP65 protection ensures resistance to moisture and dust, making the tape work both inside and outside.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 9.6 W / m
Voltage	• 12 V DC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IEC protection class	III
Cutting section	2,5 cm
Luminous efficacy	100
The lumen maintenance factor	0,96
Lifetime L70B50	30 000 h
Dimmable function	PWM

Parameter	Value
Wire length	200 mm
Luminous flux (lm)	960
Current (Im)	0,8
Beam angle	120
LED type	SMD 2835
LED quantity	600
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (lm)	120
Type of adhesive tape	3M 300 LSE
Ambient temperature suitable for operation	-20÷45
Height	3 mm


LED line LITE

Code: 477040


EAN: 5907777477040

**LED strip 600/5m SMD 12V 4000K 9,6W
IP65 8mm 5m 960lm/m LITE**

Technical drawing






Light distribution



Additional product photos

Logistics data



Single packaging

Quantity	5 m
Width	180 mm
Height	20 mm
Length	180 mm
Weight	0,171 kg

Bulk packaging

Quantity	40
Width	320 mm
Height	180 mm
Length	360 mm
Volume	0,020 m ³
Weight	7,66 kg
Comments	

Europallet

Quantity	2400
Height	1,90 m
Quantity in layer	240
Number of layers	10
Bulk quantity	60
Weight	485 kg

LED line LITE

Code: 477040

EAN: 5907777477040

**LED strip 600/5m SMD 12V 4000K 9,6W
IP65 8mm 5m 960lm/m LITE**

Example application