

LED line LITE G9 8W 3000K 750lm 220-240V



Voltage range and voltage type



LED type




Beam angle



Lifespan

Parameter	Value
Luminous efficacy	94 lm/W
Power	8 W
Colour of the light	White
Energy efficiency class 2019/2015	F
Luminous flux	750 lm
Correlated colour temperature	3000 K
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
Dimmable function	No
Survival factor	0.9
Lifetime L70B50	30 000
Supply voltage range and voltage type	220-240 AC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	white
The lumen maintenance factor	96
Lamp's diameter	19
Beam angle	270 °
Material (housing)	Ceramic
LED type	SMD2835
Lifespan	30000
Power Factor	0,5
Number of on/off cycles	50000


Parameter	Value
Colour consistency in McAdam ellipses	≤6
For indoor use	Inside
Full box quantity	500 pc
Lamp's warm-up time to 60%	1
Height	63 mm
Product weight with packaging (g)	23 g
Master carton weight (kg)	11,5
EPREL ID	1 551 402
Date of first placement on the market	2023-07-25 18:25:27
Energy class	A+
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	MLS
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
R9 colour rendering index value (EPREL)	4
Total luminous flux (EPREL)	750
On-mode power Pon (EPREL)	8
Useful luminous flux Φuse (EPREL)	750
Beam angle in degrees (EPREL)	270



Single packaging



Bulk packaging



500

Europallet

