

LED line LITE

Code: 202849

EAN: 5905378202849

**LED line LITE Downlight EASY FIX PRO
18W 1800lm CCT 3000-5000K round**



Technical data

Parameter	Value
Luminous efficacy	100 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	1800 lm
Colour consistency in McAdam ellipses	≤6
IP protection rating	IP20
Warranty (years)	3
Dimmable function	PWM
Survival factor	0.9
Lifetime L70B50	25 000
Weight	350 g
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White
The lumen maintenance factor	96 %
Lamp's diameter	217
Beam angle	110 °

Parameter	Value
Material (cover)	polycarbonate
LED type	SMD2835
LED quantity	168
Power Factor	0,7
Number of on/off cycles	20000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
Mounting hole diameter	55-175 mm
For indoor use	Inside
IEC protection class	II
IK protection rating	05
Lamp's warm-up time to 60%	1
Height	19,5 mm
Power	• 18 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 3000 K • 4000 K • 5000 K

LED line LITE

Code: 202849


EAN: 5905378202849

**LED line LITE Downlight EASY FIX PRO
18W 1800lm CCT 3000-5000K round**




Dimensions

Light distribution

Additional product photos



Logistics data



Single packaging

Width	40 mm
Height	222 mm mm
Length	235 mm mm
Weight	0,46 kg kg
	1

Bulk packaging

Number of pieces/tape in meters pack zb	20 szt.
Width	432 mm mm
Height of collective packaging	466 mm
Length	255 mm mm
Weight	12,5 kg kg
Volume	0,051 m3 m3

Europallet

Quantity collective euro pallet	480 szt.
Weight of a euro pallet	300 kg
Pallet height	1864 mm
Quantity in 1 layer	120 szt.
Number of layers	4

LED line LITE

Code: 202849

EAN: 5905378202849

**LED line LITE Downlight EASY FIX PRO
18W 1800lm CCT 3000-5000K round**

Example application