

LED line PRIME

Code: 479600-AW3HAT

EAN: 5905378212213

LINKER TRI-PROOF 55W 8250lm 4000K
IP65 150cm Emergency module 3H AT
PRIME



Technical data

Parameter	Value
Operating time in emergency mode	3 h
Emergency module test	Autotest
ULOR	3 %
Luminous efficacy	150 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	8250 lm
Colour consistency in McAdam ellipses	≤6
IP protection rating	IP65
Warranty (years)	5
Dimmable function	PWM
Survival factor	0.9
Lifetime L70B50	100 000
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80

Parameter	Value
Colour	Grey
The lumen maintenance factor	96 %
Beam angle	120 °
Material (cover)	polycarbonate
Material (housing)	Polycarbonate
Lifespan	100000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-25 ÷ 45 °C
IEC protection class	II
Lamp's warm-up time to 60%	1
Power	• 55 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K

LED line PRIME

Code: 479600-AW3HAT

EAN: 5905378212213


LINKER TRI-PROOF 55W 8250lm 4000K
IP65 150cm Emergency module 3H AT
PRIME

Dimensions

Light distribution


Additional product photos

Logistics data




Single packaging

Width	70 mm
Height	1520 mm mm
Length	60 mm mm
Weight	1,7 kg kg



Bulk packaging

Number of pieces/tape in meters pack zb	12 szt.
Width	240 mm mm
Height of collective packaging	1520 mm
Length	280 mm mm
Weight	20,75 kg kg
Volume	0,102 m3 m3



Europallet

Number of pieces/tapes in meters euro pallet	144
Quantity collective euro pallet	144 szt.
Weight of a euro pallet	249 kg kg
Pallet height	1520 mm
Quantity in 1 layer	144 szt.
Number of layers	1

LED line PRIME

Code: 479600-AW3HAT

EAN: 5905378212213

**LINKER TRI-PROOF 55W 8250lm 4000K
IP65 150cm Emergency module 3H AT
PRIME**

Example application