

LED line PRIME

Code: 200180-CAW3HAT

EAN: 5905378219960

Panel Backlit 40W 4000K 4800lm
60x60 Emergency module 3h autotest
PRIME



The 40 W Backlit PRIME panel and 4800 lm light stream are a perfect solution for modern interiors. Its neutral colour of light 4000 K provides pleasant lighting, and a wide lighting angle of 120° guarantees uniform distribution of light. The product is equipped with an automatic emergency module that runs for 3 hours.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Energy class	A+
Warranty	5
Power	• 40 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	120
Luminous flux	4800
The lumen maintenance factor	96
Lifetime L70B50	75 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6
Emergency module test	Autotest
Operating time in emergency mode	3 h
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD LED 2835
LED quantity	48
Power Factor	0,9
Number of on/off cycles	25000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-25÷45
For indoor use	Inside
Colour	white
Material (housing)	Aluminium
Material (cover)	Polystyrene

LED line PRIME

Code: 200180-CAW3HAT



EAN: 5905378219960

**Panel Backlit 40W 4000K 4800lm
60x60 Emergency module 3h autotest
PRIME**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 200180-CAW3HAT

EAN: 5905378219960

**Panel Backlit 40W 4000K 4800lm
60x60 Emergency module 3h autotest
PRIME**

Example application

