

LED line LITE LED bulb E14 6W 4000K 720lm 220-240V FILAMENT C35 CANDLE



High user-safety guaranteed.



Manufacturer issues a 3-year warranty for this product.



Beam angle



Ambient temperature suitable for operation



LED type



LED quantity



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Voltage range and voltage type



Lamp type




Lifespan

| Parameter | Value |
|---------------------------------------|-------------|
| Luminous efficacy | 120 lm/W |
| Power | 6 W |
| Colour of the light | White |
| Energy efficiency class 2019/2015 | E |
| Luminous flux | 720 lm |
| Correlated colour temperature | 4000 K |
| Colour consistency in McAdam ellipses | ≤6 |
| IP protection rating | 20 |
| Warranty (years) | 3 |
| Survival factor | 0.9 |
| Lifetime L70B50 | 25 000 |
| Weight | 14 g |
| Material | Glass |
| Supply voltage range and voltage type | 220-240 VAC |
| Frequency of the supply voltage | 50/60Hz |
| Colour rendering index Ra | 80 |
| The lumen maintenance factor | 96 % |


| Parameter | Value |
|--|-----------|
| Lamp's type | C35 |
| Lamp's diameter | 35 |
| Beam angle | 360 ° |
| Material (cover) | glass |
| LED type | Filament |
| LED quantity | 4 |
| Lifespan | 25000 |
| Number of on/off cycles | 50000 |
| Colour consistency in McAdam ellipses | ≤6 |
| Ambient temperature suitable for operation | -20÷40 °C |
| For indoor use | Inside |
| Full box quantity | 100 pc |
| Lamp's warm-up time to 60% | 1 |
| Height | 98 mm |
| Product weight with packaging | 24 g |
| Master carton weight (kg) | 3 |

Single packaging




| | |
|--------|---------|
| Width | 60 mm |
| Height | 125 mm |
| Length | 60 mm |
| Weight | 0,02 kg |
| | 1 |

Bulk packaging



| | |
|--------------------------------------|----------------------|
| Number of pieces/tape in meters pack | 100 szt. |
| Width | 380 mm |
| Height of collective packaging | 225 mm |
| Length | 200 mm |
| Weight | 2,49 kg |
| Volume | 0,017 m ³ |

Europallet



| | |
|---------------------------------|-----------|
| Quantity collective euro pallet | 9600 szt. |
| Weight of a euro pallet | 239,04 kg |
| Pallet height | 1800 mm |
| Quantity in 1 layer | 1200 szt. |
| Number of layers | 8 |