

LED line LITE

Code: 200784

EAN: 5905378200784

**DOWNLIGHT MOLLY 4000K 12W 1250lm
round IP20 White LITE**



LED Downlight MOLLY 12W 1250lm 4000K from LED line LITE is an elegant setting with minimalistic design. It is characterized by high light performance of 105 lm/W and Ra >80 color rendering, which ensures faithful color reproduction. IP20 leak class and polycarbonate housing material guarantee durability and aesthetics.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	3
Power	• 12 W
Voltage	• 170-260 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	05
IEC protection class	II
Luminous efficacy	105
Luminous flux	1250
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	110
LED type	SMD LED 2835
LED quantity	45
Power Factor	≥0,5
Number of on/off cycles	20000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Mounting hole diameter	120-135
Height	26
Fixture's diameter	145 mm
Colour	White
Material (housing)	Polycarbonate


LED line LITE

Code: 200784


EAN: 5905378200784

**DOWNLIGHT MOLLY 4000K 12W 1250lm
round IP20 White LITE**

Technical drawing




Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	151 mm
Height	37 mm
Length	150 mm
Weight	0,143 kg

Bulk packaging

Quantity	60
Width	390 mm
Height	322 mm
Length	473 mm
Volume	0,043 m3
Weight	9,9 kg

Europallet

Quantity	1800
Height	1,7 m
Quantity in layer	360
Number of layers	5
Bulk quantity	30
Weight	327 kg

LED line LITE

Code: 200784

EAN: 5905378200784

**DOWNLIGHT MOLLY 4000K 12W 1250lm
round IP20 White LITE**

Example application

