



Code: LL-20-12 EAN: 5907777479181

LED power supply LED line PRIME LL-20-12 IP67 12V

Waterproof switching power supplies of the LL series by LED line will prove themselves in many, even the most demanding applications. They are characterized by small dimensions, low weight, and thanks to the installation holes, they are easy to install.

- · Constant voltage power supply
- · Universal input voltage range
- · Protections: Short circuit / Overcurrent / Overvoltage
- · Free air cooling
- · Full load tested
- · Protection class II, power class 2 according to UL1310
- · Degree of protection IP67



MAX -30÷50 °C


Ambient temperature suitable for operation

Parameter	Value
Output power	20W
Output voltage	12V
Output current range	0 ÷ 2A
Warranty (years)	5
Input voltage range	90 ÷ 265V AC
Input voltage frequency range	47 ÷ 63Hz
Rated current	2A
Safety standards	IP67
Efficiency	0,83

Parameter	Value
Voltage tolerance	-/+5.0%
Ambient humidity	20 ÷ 90%
Insulation strength	3kVAC
EMC standards	EN55015
Mounting type	surface
Inrush current (typ.)	15A/230VAC
Ambient temperature suitable for operation	-30÷50 °C
IEC protection class	II




Single packaging




Width	45
Height	30
Length	165
Weight	0,2
	1

Bulk packaging



Number of pieces/tape in meters pack zb
Width
Height of collective packaging
Length
Weight

Europallet



Number of pieces/tapes in meters euro pallet	
Quantity collective euro pallet	32
Weight of a euro pallet	730
Pallet height	1020