

LED line PRIME

Code: LL-20-12

EAN: 5907777479181

Power Supply 20-12 IP67 20W 12V PRIME

The PRIME 20-12 IP67 12V LED line power supply is a high-performance power supply with 20W output, designed to operate in difficult weather conditions thanks to IP67 leak class. It is characterized by a wide range of input voltage from 90 to 265V AC and a stable output voltage of 12V DC. High efficiency at 0.83 and a power factor PF of 0.95 ensure efficient use of energy.



Technical data

Parameter	Value
Warranty	5
Power	• 20 W
Voltage	• 90-265 V AC
IEC protection class	II
Output current range	0 ÷ 2A
Input voltage frequency range	47 ÷ 63Hz
Rated current	2A
Safety standards	IP67
Efficiency	0,83

Parameter	Value
Voltage tolerance	-/+5.0%
Ambient humidity	20 ÷ 90%
Insulation strength	3kVAC
EMC standards	EN55015
Mounting type	surface
Inrush current (typ.)	15A / 230VAC
Ambient temperature suitable for operation	-30 ÷ 50
Output voltage	• 12 V


LED line PRIME

Code: LL-20-12

EAN: 5907777479181


**Power Supply 20-12 IP67 20W 12V
PRIME**

Technical drawing






Light distribution

Additional product photos



Logistics data



Single packaging

Quantity	1
Width	45 mm
Height	30 mm
Length	165 mm
Weight	0,21 kg

Bulk packaging

Quantity	100
Width	290 mm
Height	230 mm
Length	345 mm
Weight	18 kg

Europallet

Quantity	3200
Height	1020 mm
Bulk quantity	32
Weight	730 kg

LED line PRIME

Code: LL-20-12

EAN: 5907777479181

**Power Supply 20-12 IP67 20W 12V
PRIME**

Example application