

LED line PRIME

Code: 206564

EAN: 5905378206564

LED line PRIME Road luminaire CAMINO
50W 3000K 6500lm




Technical data

Parameter	Value	Parameter	Value
ULOR	0 %	LED type	LUMILEDS 2835
Luminous efficacy	130 lm/W	LED quantity	96
Colour of the light	White	Power Factor	0,9
Energy efficiency class 2019/2015	D	Colour consistency in McAdam ellipses	≤6
Luminous flux	6500 lm	Ambient temperature suitable for operation	-40÷50 °C
Colour consistency in McAdam ellipses	≤6	For indoor and outdoor use	YES
IP protection rating	IP66	IEC protection class	I
Warranty (years)	5	IK protection rating	08
Survival factor	0.9	Lamp's warm-up time to 60%	1
Lifetime L70B50	100 000	Length	514 mm
Frequency of the supply voltage	50/60Hz	Width	200 mm
Colour rendering index Ra	70	Height	80 mm
The lumen maintenance factor	96 %	Power	• 50 W
Beam angle	150 x 110 °	Voltage	• 220-240 V AC
Material (cover)	tempered glass	Correlated colour temperature	• 3000 K
Material (housing)	aluminum		

LED line PRIME Road luminaire CAMINO
50W 3000K 6500lm


Dimensions

Light distribution




Additional product photos

Logistics data




Single packaging

Width	514 mm
Height	80 mm mm
Length	200 mm mm
Weight	2,3 kg kg



Bulk packaging

Number of pieces/tape in meters pack zb	1 szt.
Width	5600 mm mm
Height of collective packaging	1160 mm
Length	2360 mm mm
Weight	
Volume	15,33 m3 m3



Europallet

Quantity collective euro pallet	96
Weight of a euro pallet	303,4 kg kg
Pallet height	184 cm
Number of layers	1

LED line PRIME

Code: 206564

EAN: 5905378206564

**LED line PRIME Road luminaire CAMINO
50W 3000K 6500lm**

Example application