


LED line® G4 COB 1,5W 6000K 120lm 12V AC/DC



Manufacturer issues a 3-year warranty for this product.



Voltage range and voltage type



LED type



LED quantity



Beam angle



Ambient temperature suitable for operation




Lifespan

Parameter	Value
Luminous efficacy	80 lm/W
Power	1,5 W
Colour of the light	White
Energy efficiency class 2019/2015	G
Luminous flux	120 lm
Correlated colour temperature	6000 K
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
Survival factor	0.9
Lifetime L70B50	30 000
Dimensions (L. x W.)	41,5mm x 11mm
Supply voltage range and voltage type	10-18 AC/DC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
The lumen maintenance factor	96 %

Parameter	Value
Beam angle	360 °
LED type	COB
LED quantity	1
Lifespan	30000
Power Factor	0,5
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
Full box quantity	500 pc
Lamp's warm-up time to 60%	1
Height	41,5 mm
Product weight with packaging	5 g
Master carton weight (kg)	5
Energy class	A++

Luminous [cd/klm]



C0 - C180 C90 - C270

Single packaging



Width	20 mm
Height	20 mm
Length	66 mm
Weight	0,003 kg
	1

Bulk packaging



Number of pieces/tape in meters pack zb	500 szt.
Width	610 mm
Height of collective packaging	235 mm
Length	150 mm
Weight	3,455 kg
	0,021
Volume	m3

Europallet



Number of pieces/tapes in meters euro pallet	54000
Quantity collective euro pallet	32000 szt.
Weight of a euro pallet	221,12 kg
Pallet height	1880 mm
Quantity in 1 layer	4000 szt.
Number of layers	8