

LED line PRIME

Code: 479600-CAW3HAT

EAN:

LINKER TRI-PROOF 55W 4000K 8250lm
150lm/W IP65 150cm CNBOP 3H AT
PRIME



LINKER 55W LED from LED line PRIME is an advanced lighting solution with high light efficiency of 150 lm/W and a total light stream of 8250 lm. Color light 4000K provides natural color reproduction ($R_a \geq 80$), which increases comfort of use. The housing is distinguished by IP65 leak class, IK08 resistance and high durability – life exceeds 100000 hours.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	<div><ul style="list-style-type: none">55 W</div>
Voltage	<div><ul style="list-style-type: none">220-240 V AC</div>
Correlated colour temperature	<div><ul style="list-style-type: none">4000 K</div>
Colour of the light	White
Colour rendering index Ra	80
IEC protection class	II
Luminous efficacy	150
Luminous flux	8250
The lumen maintenance factor	96
Lifetime L70B50	100 000 h
Survival factor	0.9
Dimmable function	PWM

Parameter	Value
Colour consistency in McAdam ellipses	≤ 6
ULOR	3 %
Emergency module test	Autotest
Operating time in emergency mode	3 h
Frequency of the supply voltage	50/60Hz
Beam angle	120
Lifespan	100 000 h
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	$-25 \div 45$
Colour	Grey
Material (housing)	Polycarbonate
Material (cover)	Polycarbonate

LED line PRIME

Code: 479600-CAW3HAT

EAN:

**LINKER TRI-PROOF 55W 4000K 8250lm
150lm/W IP65 150cm CNBOP 3H AT
PRIME**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 479600-CAW3HAT

EAN:

**LINKER TRI-PROOF 55W 4000K 8250lm
150lm/W IP65 150cm CNBOP 3H AT
PRIME**

Example application