

LED line PRIME

Code: 206519-DALI

EAN: 5905378218789

**Backlit Panel 4000K 34W 4760lm IP20  
30x120cm white UGR<19 PRIME DALI**



The PRIME Backlit LED panel with a power of 34 W and a light color of 4000 K is an advanced lighting fixture that provides a luminous flux of 4760 lm. Thanks to backlit technology, the SMD LED 2835 diodes placed in the housing allow for even light distribution, resulting in excellent color rendering ( $Ra \geq 80$ ).

The panel features an L70B50 lifespan of up to 50,000 hours and a low glare rating of UGR<19, which enhances user comfort.



**Technical data**

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 34 W
Voltage	• 200-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	03
IEC protection class	II
Luminous efficacy	140
Luminous flux	4760
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9
Dimmable function	Dali

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	90
LED type	SMD LED 2835
LED quantity	72
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	3,3 cm
Colour	white
Material (housing)	Aluminium
Material (cover)	Polystyrene
DALI	• YES

LED line PRIME

Code: 206519-DALI

EAN: 5905378218789

**Backlit Panel 4000K 34W 4760lm IP20  
30x120cm white UGR<19 PRIME DALI**




Technical drawing

Light distribution

Additional product photos



**Logistics data**



**Single packaging**

Quantity	1
Width	32 mm
Height	305 mm
Length	1245 mm
Weight	1,56 kg

**Bulk packaging**

Quantity	5
Width	180 mm
Height	330 mm
Length	1265 mm
Volume	0,075 m3
Weight	10,5 kg
Comments	

**Europallet**

Quantity	70
Height	1450 mm
Quantity in layer	70
Number of layers	1
Bulk quantity	70
Weight	150 kg

LED line PRIME

Code: 206519-DALI

EAN: 5905378218789

**Backlit Panel 4000K 34W 4760lm IP20  
30x120cm white UGR<19 PRIME DALI**

**Example application**

