

LED line PRIME

Code: 206519-DALI

EAN: 5905378218789

LED line PRIME Panel Backlit 34W  
4000K 4760lm UGR<19 1195x295



The PRIME Backlit LED panel with a power of 34 W and a light color of 4000 K is an advanced lighting fixture that provides a luminous flux of 4760 lm. Thanks to backlit technology, the SMD LED 2835 diodes placed in the housing allow for even light distribution, resulting in excellent color rendering ( $Ra \geq 80$ ).

The panel features an L70B50 lifespan of up to 50,000 hours and a low glare rating of  $UGR<19$ , which enhances user comfort.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 34 W
Voltage	• 200-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	03
IEC protection class	II
Luminous efficacy	140
Luminous flux	4760
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	PWM
Colour consistency in McAdam ellipses	$\leq 6$
Frequency of the supply voltage	50/60Hz
Beam angle	90
LED type	SMD LED 2835
LED quantity	72
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Colour	white
Material (housing)	Aluminium
Material (cover)	Polystyrene

LED line PRIME

Code: 206519-DALI

EAN: 5905378218789

**LED line PRIME Panel Backlit 34W  
4000K 4760lm UGR<19 1195x295**

Technical drawing

Light distribution


Additional product photos




**Logistics data**



**Single packaging**



**Bulk packaging**



**Europallet**

LED line PRIME

Code: 206519-DALI

EAN: 5905378218789

**LED line PRIME Panel Backlit 34W  
4000K 4760lm UGR<19 1195x295**

**Example application**

